

Walprime

Acrylic wall primer



Description

Walprime is a styrene-acrylic based pigmented primer recommended for masonry walls. It is a single component, water miscible primer recommended for all types of Dr.Cipy wallings.

Uses

- As a universal primer for all types of wall coating application

Key features

- Excellent adhesion
- Penetrating properties
- Water thinnable
- Excellent bond to Acrylic, PUD and PU top coats



Certified

Properties

Type	: Water miscible primer	Mixing ratio	: Single component
Finish	: Smooth and uniform	Colour	: White
Volume solids ASTM D 2697	: 36%	Recommended WFT ASTM D 4414	: 84 microns
Drying time ASTM D 1640		Recommended DFT ASTM D 7091	: 30 microns
Surface dry	: ≥ 30 minutes	Application	: By roller / brush
Tack free dry	: ≥ 2 hrs		
Hard dry	: ≥ 24 hrs		
Recommended Clean up	: Water	Shelf life	: 12 months in the unopened container

Directions to use

Sand the surface with sand paper No. 100. Stir Walprime well. Apply Walprime by brush. Re-apply after 1 hour. Allow to cure for 2-3 hrs. The primed surface is now ready to receive the putty / top coat.

Packaging and theoretical coverage

Walprime is available in 20 litre packings and has a maximum shelf life of 12 months in the un-opened containers. 1 litre of Walprime covers 12 sq m @ 30 microns

Storage and handling

The product should be stored in accordance with national regulations. It should be kept in a cool, well ventilated area, away from heat, direct sunlight, sparks and children. Handle with care. Use the mix solution within the pot life time.

Note : The typical physical properties given above are derived from testing in a controlled laboratory environment. Results derived from testing field-applied samples may vary, dependent on actual site conditions

Walprime

Acrylic wall primer



Health and safety precautions

Please refer to MSDS. Observe reasonable care and employ ordinary hygienic principles such as washing the hands with soap and water before eating or smoking. It is recommended to wear gloves, goggles and nose masks while application. In case of splashes on the skin, dampen the cloth with thinner PUT 503 and wipe the hands with the cloth. Wash then with soap and water. Dried film is non toxic. In case of contact with eyes, rinse with plenty of water and seek medical advice. In case of continuous exposure to vapour, the applicator should be immediately moved to get fresh air. The disposal of excess or waste material should be carried out in accordance with the local legislations.

Other Products Categories available Dr.Cipy brings you the widest range of Flooring Systems

